



WCT-M60C

Personal Payment Terminal



Unprecedented Security

PCI PTS 5.x certified MPOS device
EMV technology and standards
Sensitive card details are never stored on the mobile phone
No clear data is stored or transmitted during the transaction process
Compliant with payment security standards, including PCI DSS, etc.



Comprehensive Solution

Works on any mobile device with MPOS M60C
No Need Mobile Operator Involvement Only Bluetooth connection is required
Accepts All EMV-Based Contact & Contactless Cards, QR Based Transaction



Fast & Frictionless

Mail-or SMS-based receipt, easy to use
Small amount payment with "TAP&GO"
Quick payment in different business areas.

Benefits For Processors With This Solution

Creates an innovative image
Reduces POS device investments
Increases penetration into small or medium size merchants

Benefits For Card Holders With This Solution

The most convenient payment method
Makes secure EMV card transaction available everywhere
Easier and faster purchases

Benefits For Merchants With This Solution

Mobile phone+MPOS becomes a real POS terminal
Accepts all EMV-based contact & contactless cards, QR based transaction
Reduces investment costs for implement the traditional POS terminal
Can be carried with you in your pocket
Creates an innovative image for your business



Specification

Processor	32-bits High-performance security processor
Memory	512KB flash, 64KB SRAM, External: 2MB flash
Display	2 inches 320*240 Color LCD display
Keypad	10 alphanumeric keys, 4 function keys, 1 power key
Magnetic Card Reader	Compliant with ISO7811, ISO7812.
	Track 1/ 2/ 3, Bi-directional Swipe
IC Card Reader	Meets EMV/ PBOC 3.0 standards
Contactless Reader	Supports ISO/ IEC 14443 Type A & B, Mifare Standards
Status Bar	4 signal lights
Communication	Bluetooth 4.0, Support Android, iOS and Windows
Interface	Micro USB
Language	Support Chinese, English, etc.
Battery	Rechargeable lithium battery, 3.7V/ 250mAh
Working Environment	Temperature: 0~ 50°C(32 ~ 122°F). Humidity: 10% ~ 90% (non-condense)
Storage Environment	Temperature: -20 ~ 70°C(-4 ~ 158°F). Humidity: 5% ~ 95% (non-condense)
Cable	USB Cable
Dimensions	120mm*65mm*17.5mm(L*W*H)
Weight	116g(include battery)
Certification	PCI PTS 5.x, EMV Contact L1&L2, EMV Contactless L1, PBOC 3.0 L1/ L2
Optional Module	Built-in 1D/ 2D Barcode Scanner



Wisecard Technology Co.,Ltd

Tel : +852 5461 1229 +86 755 86007346 Email : sales@wisecardtech.com Http : www.wisecardtech.com
1-602,Shenzhen Software Park, Hi-Tech Middle 2nd RD, Nanshan, Shenzhen, 518057, China

